

## Datenblatt Kantenschutz flexibel

Technical data sheet flexible Edge protector

Stand: 04.2013

Artikel Nr. (Article No.)

307889

### Beschreibung (description)

Flexibles Kantenschutzprofil zur Verkleidung und Verzierung von Kanten, bestehend aus U-förmigem metallinem Gerüstband mit PVC- Ummantelung.

Bei der Montage wird das Profil von Hand auf die zu umkleidenden Kanten aufgedrückt. Durch die Klemmwirkung der PVC- Lippen des PVC- Mantels und durch die Verzahnung des Stahlgerüstbandes ist sichere Klemmwirkung gegeben.

Klebstoffe und besondere Befestiger, sowie zusätzliche Werkzeuge sind nicht erforderlich.

Profil ist witterungsbeständig und temperaturfest innerhalb eines Bereiches von - 40°C bis +90°C.

*Flexible edge protector for covering and decorating sharp edges, consisting of a u-shaped metal insert strip and a PVC coating.*

*At assembling the profile is pressed into place by hand. The profile is held securely in place by the clamping effect provided by the lips in the PVC coating and by the teeth in the metal insert.*

*There is no need for adhesives, other fastening aids or additional tools.*

*Section is resistant to weathering and can be used within a temperature range from -40°C up to +90°C.*


### Produktaufbau (assembly)

Profilkörper PVC Qualität 911V5 ALD

Gerüstband Stahl 1.0347

### Abmaße

Klemmbereich (Clamping range) 1-2 [mm]



Mindestbiegeradien [mm]  
minimum bending radii [mm]

### Allgemein

mit eingebettetem Stahlgerüstband (with embedded steel insert)

Farbe (colour) schwarz (black)

### Richtlinien (directives)

Altauto - RL 2000/53/EG (EC)	Konform	(compliant)
PAK-Einstufung	Kategorie 1 [Summe 16 PAK (EPA) mg/kg (<0,2)] *ZEK 01.2-08	(Category 1 [total 16 PAK (EPA) mg/kg (<0,2)] *ZEK 01.2-08)
Verwendung von REACH (SVHC) Stoffe (use of SVHC-substances)	Nein oder unterhalb der Grenzwerte nach REACH	(No or underneath the limit values after REACH)
REACH	Konform	(compliant)
RoHS - RL 2002/95/EG (EC)	Konform	(compliant)

